CLAIMS

What is claimed is:

1	1.	An	automated	laser	weld	machine	that	wel	ds
---	----	----	-----------	-------	------	---------	------	-----	----

- 2 together at least two photonic package components,
- 3 comprising:
- a laser station that can weld the photonic package components; and,
 - an automated handling assembly that can load and unload the photonic package components in said laser station.
- 1 2. The machine of claim 1, wherein the photonic
- 2 package components include a package and a fiber sleeve
 - 3 that are located in a horizontal position, said laser
 - 4 station includes three lasers that weld the fiber sleeve to
 - 5 the package.
 - 1 3. The machine of claim 2, wherein said laser station
 - 2 includes a package tooling that holds the package, said

- 3 package tooling having a yoke that can rotate about two
- 4 orthogonal axis.
- 1 4. The machine of claim 3, wherein said package tooling
- 2 includes an actuator to assert a biasing force to said
- 3 yoke.
- 1 5. The machine of claim 3, wherein said package
- 2 tooling includes a vibrator to apply vibratory energy to
- 3 said yoke.
- 1 6. The machine of claim 3, wherein said package
- 2 tooling includes a friction band that can lock a position
- 3 of said yoke.
- 7. The machine of claim 6, wherein said package
- 2 tooling includes a vacuum channel that pulls said friction
- 3 band into said yoke.
- 1 8. The machine of claim 6, wherein said package
- 2 tooling has a vacuum channel that pulls said friction band
- 3 away from said yoke.

- 9. The machine of claim 3, wherein said package
- 2 tooling has a plurality of first electrical contacts that
- 3 can be coupled to the package, and an actuator that moves
- 4 said electrical contacts.
- 1 10. The machine of claim 9, wherein said package
- 2 tooling includes a plurality of second contacts that can be
- 3 coupled to said first contacts, and an actuator to move
- 4 said second contacts relative to said yoke.
- 1 11. The machine of claim 6, wherein said package
- 2 tooling includes a pair of rotary coupling that are pulled
- 3 into said yoke with a vacuum pressure.
- 1 12. The machine of claim 3, wherein said laser station
- 2 includes a fiber tooling that holds the fiber sleeve.
- 1 13. The machine of claim 12, wherein said fiber
- 2 tooling includes an actuator to move the fiber sleeve into
- 3 the package.

- 1 14. The machine of claim 13, wherein said actuator can
- 2 vary a force applied by the fiber sleeve to the package.
- 1 15. An automated laser weld machine that welds
- 2 together at least two photonic package components,
- 3 comprising:
- station means for laser welding the photonic package components; and,
 - handling means for loading and unloading the photonic package components in the station means.
 - 16. The machine of claim 15, wherein the photonic package components include a package and a fiber sleeve
- 3 that are located in a horizontal position, said station
- 4 means includes three lasers that weld the fiber sleeve to
- 5 the package.
- 1 17. The machine of claim 16, wherein said station
- 2 means includes a package tooling that holds the package,

- 4 two orthogonal axis.
- 1 18. The machine of claim 17, wherein said package
- 2 tooling includes an actuator to assert a biasing force to
- 3 said yoke.
- 1 19. The machine of claim 17, wherein said package
- 2 tooling includes a vibrator to apply vibratory energy to
- 3 said yoke.

- 1 20. The machine of claim 17, wherein said package
- 2 tooling includes a friction band that can lock a position
- 3 of said yoke.
- 1 21. The machine of claim 20, wherein said package
- 2 tooling includes a vacuum channel that pulls said friction
- 3 band into said yoke.
- 1 22. The machine of claim 20, wherein said package
- 2 tooling has a vacuum channel that pulls said friction band
- 3 away from said yoke.

- 1 23. The machine of claim 17, wherein said package
- 2 tooling has a plurality of first electrical contacts that
- 3 can be coupled to the package, and an actuator that moves
- 4 said electrical contacts.
- 1 24. The machine of claim 23, wherein said package
- 2 tooling includes a plurality of second contacts that can be
- 3 coupled to said first contacts, and an actuator to move
- 4 said second contacts relative to said yoke.
- 1 25. The machine of claim 17, wherein said package
 - tooling includes a pair of rotary couplings that are pulled
- 3 into said yoke with a vacuum pressure.
- 1 26. The machine of claim 17, wherein said laser
- 2 station includes a fiber tooling that holds the fiber
- 3 sleeve.
- 1 27. The machine of claim 26, wherein said fiber
- 2 tooling includes an actuator to move the fiber sleeve into
- 3 the package.

- An automated laser weld machine that welds 1
- together at least two photonic package components, 2
- 3 comprising:

- a first fixture that can a hold first photonic package 4 9543644 BANGE component in a horizontal position;
 - a second fixture that can hold a second photonic package component in a horizontal position adjacent to the first photonic package component;
- **l** ≥ 9 a first laser that can emit a light beam to weld the 10 first and second photonic package components;
 - a second laser that can emit a light beam to weld the 11
 - first and second photonic package components; and, 12
 - a third laser that can emit a light beam to weld the 13
 - 14 first and second photonic package components.

Atty Docket No. 155603-0177 Express Mail Label No. EL666211491US 413921

- 1 30. The machine of claim 29, wherein the first
- 2 photonic package component is a package and the second
- 3 photonic package component includes a fiber sleeve attached
- 4 to a fiber.
- 1 31. The machine of claim 30, wherein said first
- 2 fixture has a yoke that can rotate about two orthogonal
- 3 axis.
- 1 32. The machine of claim 31, wherein said first fixture
- 2 includes an actuator to assert a biasing force to said
- 3 yoke.
- 1 33. The machine of claim 31, wherein said first
- 2 fixture includes a vibrator to apply vibratory energy to
- 3 said yoke.
- 1 34. The machine of claim 31, wherein said first
- 2 fixture includes a friction band that can lock a position
- 3 of said yoke.

- 1 35. The machine of claim 34, wherein said first
- 2 fixture includes a vacuum channel that pulls said friction
- 3 band into said yoke.
- 1 36. The machine of claim 35, wherein said first
- 2 fixture has a vacuum channel that pulls said friction band
- 3 away from said yoke.
 - 37. The machine of claim 31, wherein said first fixture has a plurality of first electrical contacts that can be coupled to the package, and an actuator that moves said electrical contacts.
- 1 38. The machine of claim 37, wherein said first
- 2 fixture includes a plurality of second contacts that can be
- 3 coupled to said first contacts, and an actuator to move
- 4 said second contacts relative to said yoke.
- 1 39. The machine of claim 34, wherein said first
- 2 fixture includes a pair of rotary couplings that are pulled
- 3 into said yoke with a vacuum pressure.

- 1 40. The machine of claim 31, wherein said second
- 2 fixture includes an actuator to move the fiber sleeve into
- 3 the package.
- 1 41. The machine of claim 40, wherein said actuator can
- 2 vary a force applied by the fiber sleeve to the package.
- 1 42. An automated laser weld machine that welds
- 2 together at least two photonic package components,
- 3 comprising:
- 4 first fixture means for holding a first photonic
- 5 package component in a horizontal position;
- 6 second fixture means for holding a second photonic
- 7 package component in a horizontal position adjacent to the
- 8 first photonic package component;
- 9 first welding means for welding the first and second
- 10 photonic package components;

- 12 photonic package components; and,
- third welding means for welding the first and second 13

second welding means for welding the first and second

- 14 photonic package components.
 - The machine of claim 42, wherein the first 1 43.
 - photonic package component is a package and the second 2
- photonic package component includes a fiber sleeve attached
- to a fiber.
- The machine of claim 43, wherein said first 44.
- fixture means includes a yoke that can rotate about two
- orthogonal axis.
 - 45. The machine of claim 44, wherein said first fixture 1
 - means includes an actuator to assert a biasing force to 2
 - 3 said yoke.
 - The machine of claim 44, wherein said first 1 46.
 - fixture means includes a vibrator to apply vibratory energy 2
 - 3 to said yoke.

-28-Atty Docket No. 155603-0177 Express Mail Label No. EL666211491US

- 1 47. The machine of claim 44, wherein said first
- 2 fixture means includes a friction band that can lock a
- 3 position of said yoke.
- 1 48. The machine of claim 47, wherein said first
- 2 fixture means includes a vacuum channel that pulls said
- 3 friction band into said yoke.
 - 49. The machine of claim 47, wherein said first fixture means includes a vacuum channel that pulls said friction band away from said yoke.
- 50. The machine of claim 44, wherein said first fixture means includes a plurality of first electrical contacts that can be coupled to the package, and an
- 4 actuator that moves said electrical contacts.
- 1 51. The machine of claim 50, wherein said first
- 2 fixture means includes a plurality of second contacts that
- 3 can be coupled to said first contacts, and an actuator to
- 4 move said second contacts relative to said yoke.

- 1
- 52. The machine of claim 44, wherein said first
- fixture means includes a pair of rotary couplings that are 2
- 3 pulled into said yoke with a vacuum pressure.
- The machine of claim 44, wherein said second 1
- fixture means includes an actuator to move the fiber sleeve 2
- 3 into the package.
- - The machine of claim 53, wherein said actuator can
 - vary a force applied by the fiber sleeve to the package.

jai

- 55. An automated laser weld machine that welds
 - together at least two photonic package components,
- **月**3 comprising:
 - a first tooling that can hold a first photonic package 4
 - 5 component in a horizontal position, said first tooling
 - having a yoke that can rotate about two orthogonal axis and 6
 - an actuator that applies a biasing force to said yoke; 7

- a second tooling that can hold a second photonic 8
- package component in a horizontal position adjacent to the 9
- 10 first photonic package component; and,
- 11 a laser that can emit a light beam to weld the first
- 12 and second photonic package components.
 - The machine of claim 55, wherein the first 1 56.
- photonic package component is a package and the second
- photonic package component includes a fiber sleeve attached
 - to a fiber.
 - The machine of claim 55, wherein said first 57.
 - tooling includes a vibrator to apply vibratory energy to
- [] [] 3 said yoke.
 - The machine of claim 55, wherein said first 1 58.
 - tooling includes a friction band that can lock a position 2
 - of said yoke. 3

- 1
- 59. The machine of claim 58, wherein said first
- tooling includes a vacuum channel that pulls said friction 2
- band into said yoke. 3
- The machine of claim 58, wherein said first 1
- tooling has a vacuum channel that pulls said friction band 2
- away from said yoke. 3
 - The machine of claim 56, wherein said first tooling has a plurality of first electrical contacts that can be coupled to the package, and an actuator that moves said electrical contacts.
 - The machine of claim 61, wherein said first 62.
- 2 fixture includes a plurality of second contacts that can be
- coupled to said first contacts, and an actuator to move . 3
 - 4 said second contacts relative to said yoke.
 - The machine of claim 55, wherein said first 1 63.
 - tooling includes a pair of rotary couplings that are pulled 2
 - into said yoke with a vacuum pressure. 3

型 型 1

- 3 the package.
- 1 65. The machine of claim 64, wherein said actuator can
- 2 vary a force applied by the fiber sleeve to the package.
- 1 66. An automated laser weld machine that welds

 1 together at least two photonic package components,
 1 comprising:
 - a first tooling that can hold a first photonic package component in a horizontal position, said first tooling having a yoke that can rotate about two orthogonal axis and biasing means for applying a biasing force to said yoke;
 - 8 a second tooling that can hold a second photonic
 - 9 package component in a horizontal position adjacent to the
- 10 first photonic package component; and,
- a laser that can emit a light beam to weld the first
- and second photonic package components.

 Atty Docket No. 155603-0177 -33
 Express Mail Label No. EL666211491US

 413921

- The machine of claim 66, wherein the first 67.
- photonic package component is a package and the second 2
- photonic package component includes a fiber sleeve attached 3
- to a fiber. 4
- The machine of claim 66, wherein said first 68. 1
- tooling includes a vibrator to apply vibratory energy to 2
- 3 said yoke.
- The machine of claim 66, wherein said first 69.
 - tooling includes a friction band that can lock a position
- of said yoke.
 - The machine of claim 69, wherein said first 70.
- tooling includes a vacuum channel that pulls said friction 2
- 3 band into said yoke.
- 71. The machine of claim 69, wherein said first 1
- tooling has a vacuum channel that pulls said friction band 2
- away from said yoke. 3

-34-Atty Docket No. 155603-0177 Express Mail Label No. EL666211491US

- 72. The machine of claim 67, wherein said first 1
- tooling has a plurality of first electrical contacts that 2
- can be coupled to the package, and an actuator that moves 3
- said electrical contacts. 4
- The machine of claim 72, wherein said first 1
- tooling includes a plurality of second contacts that can be 2
- coupled to said first contacts, and an actuator to move
- said second contacts relative to said yoke.
 - The machine of claim 66, wherein said first 74.
 - tooling includes a pair of rotary couplings that are pulled
 - into said yoke with a vacuum pressure.
 - The machine of claim 67, wherein said second
 - tooling includes an actuator to move the fiber sleeve into 2
 - 3 the package.

j-A

- 1 The machine of claim 75, wherein said actuator can
- 2 vary a force applied by the fiber sleeve to the package.

- 1 77. An automated laser weld machine that welds
- 2 together at least two photonic package components,
- 3 comprising:
- 4 a first tooling that can hold a first photonic package
- 5 component in a horizontal position, said first tooling
- 6 having a yoke that can rotate about two orthogonal axis and
- a friction band that can lock and unlock said yoke;
 - a second tooling that can hold a second photonic package component in a horizontal position adjacent to the first photonic package component; and,
 - a laser that can emit a light beam to weld the first and second photonic package components.
 - 1 78. The machine of claim 77, wherein the first
 - 2 photonic package component is a package and the second
 - 3 photonic package component includes a fiber sleeve attached
 - to a fiber. 4

- 1 79. The machine of claim 77, wherein said first
- 2 tooling includes a vibrator to apply vibratory energy to
- 3 said yoke.

j mè

- 1 80. The machine of claim 77, wherein said first
- tooling includes a vacuum channel that pulls said friction 2
- band into said yoke.
- 81. The machine of claim 77, wherein said first tooling has a vacuum channel that pulls said friction band away from said yoke.
- The machine of claim 78, wherein said first П 2 tooling has a plurality of first electrical contacts that 3 can be coupled to the package, and an actuator that moves 4 said electrical contacts.
 - 1 The machine of claim 82, wherein said first
 - 2 tooling includes a plurality of second contacts that can be
 - 3 coupled to said first contacts, and an actuator to move
 - 4 said second contacts relative to said yoke.

- 2 tooling includes a pair of rotary couplings that are pulled
- 3 into said yoke with a vacuum pressure.
- 1 85. The machine of claim 78, wherein said second
- 2 tooling includes an actuator to move the fiber sleeve into
- 3 the package.

⊨

413921

- 86. The machine of claim 85, wherein said actuator can vary a force applied by the fiber sleeve to the package.
- 87. An automated laser weld machine that welds together at least two photonic package components, comprising:
- a first tooling that can hold a first photonic package
- 5 component in a horizontal position, said first tooling
- 6 having a yoke that can rotate about two orthogonal axis and
- 7 lock means for locking and unlocking said yoke;

Atty Docket No. 155603-0177 -38-Express Mail Label No. EL666211491US

- 8 a second tooling that can hold a second photonic
- 9 package component in a horizontal position adjacent to the
- 10 first photonic package component; and,
- a laser that can emit a light beam to weld the first
- 12 and second photonic package components.
 - 1 88. The machine of claim 87, wherein the first
- 2 photonic package component is a package and the second
- 3 photonic package component includes a fiber sleeve attached
- photonic pa
 photonic pa
 photonic pa
 photonic pa
 to a fiber.

 1 89. The
 top a second part of the part o
 - 1 89. The machine of claim 87, wherein said first
 - 2 tooling includes a vibrator to apply vibratory energy to
- □ 3 said yoke.

ᅶ

- 1 90. The machine of claim 87, wherein said lock means
- 2 includes a friction band that is pulled into said yoke.
- 1 91. The machine of claim 90, wherein said lock means
- 2 includes a vacuum channel that pulls said friction band
- 3 away from said yoke.

Atty Docket No. 155603-0177 -39-Express Mail Label No. EL666211491US

]=b

- 1 92. The machine of claim 88, wherein said first
- 2 tooling has a plurality of first electrical contacts that
- 3 can be coupled to the package, and an actuator that moves
- 4 said electrical contacts.
- 1 93. The machine of claim 92, wherein said first
- 2 tooling includes a plurality of second contacts that can be
- 3 coupled to said first contacts, and an actuator to move
- 4 said second contacts relative to said yoke.
- 1 94. The machine of claim 87, wherein said first
- 2 tooling includes a pair of rotary couplings that are pulled
 - into said yoke with a vacuum pressure.
- 1 95. The machine of claim 87, wherein said second
- 2 tooling includes an actuator to move the fiber sleeve into
- 3 the package.
- 1 96. The machine of claim 95, wherein said actuator can
- 2 vary a force applied by the fiber sleeve to the package.

- 1 97. An automated laser weld machine that welds
- 2 together at least two photonic package components,
- 3 comprising:

==

- 4 a first tooling that can hold a first photonic package
- component in a horizontal position, said first tooling 5
- 6 having a yoke that can rotate about two orthogonal axis, a
- first plurality of contacts that can engage the package, a
- second plurality of contacts, and an actuator that can move
 - said second plurality of contacts into said yoke so that
 - said second plurality of contacts are electrically coupled
 - to said first plurality of contacts;
 - a second tooling that can hold a second photonic
 - 13 package component in a horizontal position adjacent to the
 - 14 first photonic package component; and,
- 15 a laser that can emit a light beam to weld the first
- 16 and second photonic package components.

- 2 photonic package component is a package and the second
- 3 photonic package component includes a fiber sleeve attached
- 4 to a fiber.
- 1 99. The machine of claim 97, wherein said first
- 2 tooling includes a vibrator to apply vibratory energy to
- said yoke.
 - 100. The machine of claim 97, wherein said first tooling includes a pair of rotary couplings that are pulled into said yoke with a vacuum pressure.
- 101. The machine of claim 98, wherein said second 2 tooling includes an actuator to move the fiber into the 3 package.
 - 102. The machine of claim 101, wherein said actuator 1
 - 2 can vary a force applied by the fiber sleeve to the
 - 3 package.

- 1 103. An automated laser weld machine that welds
- 2 together at least two photonic package components,
- 3 comprising:
- 4 a first tooling that can hold a first photonic package
- 5 component, said first tooling having a yoke that can rotate
- 6 about two orthogonal axis, a first plurality of contacts
- 7 that can engage the package, and actuator means for
- B coupling a second plurality of contacts to said first
- 8 coupling a second plur
 9 plurality of contacts;
 10 a second tooling to package component adja

- a second tooling that can hold a second photonic package component adjacent to the first photonic package component; and
- a laser that can emit a light beam to weld the first
- 14 and second photonic package components.
 - 1 104. The machine of claim 103, wherein the first
 - 2 photonic package component is a package and the second

- 4 to a fiber.
- The machine of claim 103, wherein said first 105. 1
- tooling includes a vibrator to apply vibratory energy to 2
- said yoke. 3
- The machine of claim 103, wherein said first 106. 1
- tooling includes a pair of rotary couplings that are pulled 2
- into said yoke with a vacuum pressure.
 - The machine of claim 104, wherein said second 107.
 - tooling includes an actuator to move the fiber sleeve into
 - the package.
 - The machine of claim 107, wherein said actuator 1
 - can vary a force applied by the fiber sleeve to the 2
 - 3 package.
 - 109. An automated laser weld machine that welds 1
 - together at least two photonic package components, 2
 - comprising: 3

- 4 a first tooling that can hold a first photonic package
- 5 component, said first tooling having a yoke that can rotate
- 6 about a plurality of bearings, a friction band that locks a
- 7 position of said yoke with a vacuum pressure that also
- 8 moves and seals said bearings;
- 9 a second tooling that can hold a second photonic
- 10 package component adjacent to the first photonic component;
- 11 and,
 12 12 13 and
 11 1

道 2

- a laser that can emit a light beam to weld the first and second photonic package components.
- 1 110. The machine of claim 109, wherein the first
 - photonic package component is a package and the second
- 3 photonic package component includes a fiber sleeve attached
- 4 to a fiber.
- 1 111. The machine of claim 109, wherein said first
- 2 tooling includes a vibrator to apply vibratory energy to
- 3 said yoke.

- The machine of claim 110, wherein said second 1
- tooling includes an actuator to move the fiber sleeve into 2
- the package. 3
- The machine of claim 112, wherein said actuator 1 113.
- can vary a force applied by the fiber sleeve to the 2
- 3 package.
- 口 旬1 114. A method for welding a first photonic package
 - component to a second photonic package component,
 - comprising:

-

- loading a first photonic package component onto a first tooling with a robotic arm;
 - 6 loading a second photonic package component onto a
 - 7 second tooling with the robotic arm; and,
 - welding the second photonic package component to the 8
 - first photonic package component. 9

- 1 115. The method of claim 114, wherein the first and
- 2 second photonic package components are welded in a
- 3 horizontal position.
- 1 116. The method of claim 115, wherein the first and
- 2 second photonic package components are welded with three
- 3 lasers.